STAR TOOL SUPPLY / GRAND TOOL SUPPLY

BORING HEAD SETS

SERIES 420:

Processing Range .2" - 10"

Rigid construction: Finest materials and craftsmanship are employed to combine strength, flexibility and accuracy in a tool of unique design. 2 vertical boring tool holes: one centered and one offset. One cross hole for greater versatility and capacity. Dependable adjustment: far spread graduations for closer reading. Perfectly balanced for high speed operation. Precision ground and hardened integral shank for rigidity and smooth operation.




Dial Readings: .01mm

Set includes boring head, fitted case, and an assortment of boring bars and holders to permit a great variety of machining operations.

| Shank | Drawbar Thread | Order No. | Price |
|-------|-------------------|-----------|-------|
| R8 | 7/16-20 | 4200105 | |
| NT40 | 5/8-11 | 4200107 | |

BORING HEADS

SERIES 420:



- capacity of a 3" Boring Head. Manufactured under rigid quality control standards to
- insure accuracy and stability. Body integrity combined with new dovetail design practi-
- cally eliminates chatter in fully extended position.
- Unconditional lifetime warranty by Manufacturer.

Specifications:

- Diameter of body: 2-1/2"
- Length of body: 3-7/16"
- Direct dial reading: .001"
- Boring capacity: up to 4"
- Standard tooling: 1/2"
- Offset: 3/4"

| Model No. | Shank | Order No. | Price |
|----------------|-----------|--------------------|-------|
| BHR8B BH34B | R8 3/4 | 4205008 4205034 | |



Tel: 201-518-8461 / Fax: 201-596-3427 650 Huyler St / So. Hackensack, NJ 07606 USA

BORING HEAD SETS

SERIES 420:



Hardended and ground adjusting screw, .001" graduations for fine adjustment, two vertical boring tool holes (one centered and one offset) and one cross hole.

Set includes:

- Boring Head
- R8 Shank
- Carbide Tipped (Steel Grade) Boring Bar Set





| Dia. | Thread Hole | Boring Tool Hole | Offset | Order No. | Price |
|-------------|---|------------------------|----------------------|-------------------------------|-------|
| 2 3 4 | 7/8 - 20" 1-1/2 - 18" 1-1/2 - 18" | 1/2" 3/4" 1" | 5/8" 1" 1-5/8" | 2395286 2395386 2395486 | |

INTEGRATED R-8 SHANK BORING HEAD

SERIES 420:



- Integrated shank for maximum rigidity.
- · Hardened and Ground body.
- Black oxide finish.

• Cross and vertical hole dia. 1/2"

Offset travel 3/4"



| Order No. | Head Diameter | Overall Length | Graduation | Price |
|-----------|---------------|-------------------|------------|-------|
| 4202128 | 2-1/2" | 7-3/16" | .0005" | |

BORING HEADS

SERIES 420:

These boring heads are of extremely high quality. The hardened and ground adjusting screw ensures utmost precision and long life. Widespread .001" graduations permit even finer adjustments. Two vertical boring tool holes (one centered and one offset) as well as a cross hole result in great versatility.



1/20/4

perior Import

| Dia. | Threaded Hole | Boring Tool Hole Size | Offset | Order No. | Price |
|------|------------------|-----------------------------|--------|-----------|-------|
| 2 | 7/8 - 20 | 1/2 | 5/8 | 2395002 | |
| 3 | 1-1/2 - 18 | 3/4 | 1 | 2395003 | |
| 4 | 1-1/2 - 18 | 1 | 1-5/8 | 2395004 | |
| 50mm | 7/8 - 20 | 12mm | 15mm | 2395001 | |

SHANKS FOR BORING HEADS

SERIES 421:



| | Order | Order No. | | | |
|-------|---------|-------------------|-------|--|--|
| Shank | 7/8-20 | 7/8-20 1-1/2 - 18 | | | |
| Size | Thread | Thread | Price | | |
| | | | | | |
| MT3 | 2400103 | 2400003 | | | |
| MT4 | 2400104 | 2400004 | | | |
| NST30 | 2400130 | 2400030 | | | |
| NST40 | 2400140 | 2400040 | | | |
| R8 | 2400100 | 2400000 | | | |
| 3/4 | 2400148 | 2400048 | | | |
| 1 | 2400164 | 2400064 | | | |

BORING HEADS WITH INTERCHANGEABLE SHANKS

SERIES 978:

| Head Dia. | Threaded Back | Hole Dia. | Overall Length | Offset Travel | Vert. Hole Spacing | Tool No. | Order No. | Price |
|--------------|------------------|--------------|-------------------|------------------|--------------------------|-------------|--------------|-------|
| 2 | 7/8-20 | 3/8 | 2-7/16 | 3/4 | 5/8 | BHTA | 9784713 | |
| 2-1/2 | 7/8-20 | 1/2 | 3-3/16 | 3/4 | 3/4 | BHTB | 9784714 | |
| 2-1/2 | 7/8-20 | 5/8 | 3-3/16 | 3/4 | 3/4 | BHTC | 9784715 | |
| 3 | 1-1/2-18 | 3/4 | 3-1/2 | 1-1/4 | 5/16 | BHTD | 9784716 | |



INTERCHANGEABLE SHANKS FOR BORING HEADS

SERIES 978:





| 7/8 — 20 THREAD | | | | | | |
|---------------------------------------|-------------|--------------|-------|--|--|--|
| Description | Tool No. | Order No. | Price | | | |
| 2 M.T. with Tang | BHQM2 | 9784717 | | | | |
| 3 M.T. with Tang | BHQM3 | 9784718 | | | | |
| 4 M.T. with Tang | BHQM4 | 9784719 | | | | |
| #30 N.T. with Draw Bar & Drive Flange | BHQS3 | 9784720 | | | | |
| #40 N.T. with Draw Bar & Drive Flange | BHQS4 | 9784721 | | | | |
| 1/2" Diameter Straight Shank | BHQ16 | 9784722 | | | | |
| 3/4" Diameter Straight Shank | BHQ24 | 9784723 | | | | |
| 1" Diameter Straight Shank | BHQ32 | 9784724 | | | | |
| R-8 Shank | BHQR8 | 9784725 | | | | |

| 1-1/2 — 18 THREAD | | | | | | |
|---------------------------------------|-------|---------|-------|--|--|--|
| | Tool | Order | | | | |
| Description | No. | No. | Price | | | |
| 3 M.T. with Tang | внхмз | 9784726 | | | | |
| 4 M.T. with Tang | BHXM4 | 9784727 | | | | |
| #30 N.T. with Draw Bar & Drive Flange | BHXS3 | 9784728 | | | | |
| #40 N.T. with Draw Bar & Drive Flange | BHXS4 | 9784729 | | | | |
| 1" Diameter Straight Shank | BHX32 | 9784730 | | | | |
| 1-1/4" Diameter Straight Shank | BHX40 | 9784731 | | | | |
| 1-1/2" Diameter Straight Shank | BHX48 | 9784732 | | | | |
| R-8 Shank | BHXR8 | 9784733 | | | | |

AUTOMATIC BORING AND FACING HEADS

SERIES 420:


With pre-set stop.

For Boring Mills, Jig Borers, Milling Machines, Radial Drills, and Lathes.

Highly accurate within .002" per 3/4" travel. Automatic facing possible without stopping spindle. Working parts hardened and ground.

| Order No. | 239 | 5102 | 2395103 | | |
|------------------------------------|---------------------------|-------|-----------|-------|--------|
| Price | | | | | |
| Diameter of body | 2- | 3/8 | | 3-1/2 | |
| Shank | R- | -8* | | R-8* | |
| Height without shank | 2-: | 3/4 | | 3-3/4 | |
| No. of feeds per revolution | 1 | 2 | 1 | 2 | 3 |
| Automatic feed | | | | | |
| (radial) per revolution | .0025" | .005" | .0025" | .005" | .0075" |
| Radial movement for one | | | | | |
| graduation or vernier | .00 | 005 | | .0005 | |
| Vertical tool positions | 3 | | | 3 | |
| Minimum capacity | 1/8 | | 13/64 | | |
| Maximum capacity | 9-3/4 13-3/4 | | | | |
| Maximum carriage movement (radial) | 3/4 1.2 | | | | |
| Maximum speed (for boring only) | 1000 RPM (RH only) 700 RF | | RPM (RH o | nly) | |
| Boring bar diameter | 1. | /2 | | 3/4 | |


*Other shanks available; please inquire.



APPLICATIONS:

Order No. 2395102 supplied with 1 wrench extension.

Order No. 2395103 supplied with 3 wrench extensions.











1 FIXED CAM FOR FEED RATE

LOCKING-SCREW

