



AEROSOLS CANNOT BE SHIPPED BY AIR



SERIES 447:

LIQUID THREADLOCKERS

262 Threadlocker

Medium to High Strength

A permanent locking threadlocker for fasteners up to 3/4" (20mm) diameter. High lubrication for easy assembly. Excellent for preventing rust and corrosion in extreme chemical/environmental conditions.

Container Size	Order No.	Price
10 ml. Tube	26221	
50 ml. Bottle	26231	
250 ml. Bottle	26241	



242[®] Threadlocker

Medium Strength

A general-purpose, removable threadlocker for fasteners between 1/4" and 3/4" (6 to 20 mm) diameters. Controlled lubricity for accurate clamp loads. Parts can be separated using hand tools.

Container Size	Order No.	Price
10 ml. Bottle	24221	
50 ml. Bottle	24231	
250 ml. Bottle	24241	



222 MS Threadlocker

Low Strength/Small Screw

Ideal for fastener diameters of 1/4" (6mm) and smaller. Controlled lubricity for accurate clamp loads. Parts can be separated using hand tools.

Container Size	Order No.	Price
10 ml. Bottle	22221	
50 ml. Bottle	22231	
250 ml. Bottle	22241	



SURFACE PREPARATION

7649 Primer N

A solvent-based primer that features very long on-part life. Decreases the set-up time of Loctite[®] Threadlockers and increases breakaway torque on most fastener surfaces. Ideal for cure conditions below room temperature.

Container Size	Order No.	Price
25 gm. Aerosol Can	21347	
1.75 fl oz. Bottle	19269	
4.5 oz. Aerosol Can	21348	



THREAD SEALANT

565 PST[®] THREAD SEALANT

Controlled Strength

A general-purpose instant sealant for tapered and straight/tapered fittings. Controlled strength for ease of disassembly.

50 ml. Tube
Order No. 56531
Price:



BONDING ADHESIVES

454 PRISM[®] Surface Insensitive Instant Adhesive Gel

A General-purpose, no-run clear gel. Can be applied to vertical surfaces. Excellent for almost all surfaces. Ideal for porous substrates and rough and acidic surfaces.

495 SUPER BONDER[®]

Instant Adhesive

A general-purpose adhesive designed to bond rubber, metal and plastic parts with gaps to .004".



Product No.	Order No.	Container Size	Price
454	9945404	3 gm Tube	
454	45440	20 gm Tube	
495	49504	3 gm Tube	
495	49550	1 oz Bottle	

COATING

Color Guard[®]

Tough Rubber Coating

Inhibits rust and corrosion; seals, insulates and identifies almost any material in minutes. Creates a non-slip gripping surface. Rubber coating won't crack or chip. Acid and alkali resistant. Lasts for years. Use to 200°F. Dip, spray or brush to apply. Suggested applications include: Tools, metal, electrical connections, masonry, wood, conveyors, glass, rope, fabric.



Size	Black	Blue	Red	Yellow	Price
14.5 oz. Can	34979	34982	34985	34988	



While we show only the popular **LOCTITE** items we can supply their entire range of products; please inquire.

SPECIALTY FLUIDS



AEROSOLS CANNOT BE SHIPPED BY AIR



SERIES 447:

LUBRICANTS



C5-A Copper Based Anti-Seize
Exclusive formula suspends copper and graphite in a high-quality grease. Protects metal parts from rust, corrosion, galling and seizing at temperatures to 1800°F (982°C). Tested to MIL-A-907.

Container Size	Order No.	Price
8 oz. Brush Top	51147	
1 lb. Brush Top	9951007	



Heavy Duty Anti-Seize
Metal-Free. Excellent lubricity. Provides outstanding lubrication to all metals including stainless steel, aluminum, and soft metals up to 2400° F (1315°C).

Container Size	Order No.	Price
9 oz. Brush Top	9951605	
1 lb. Brush Top	9951606	



Nickel Anti-Seize
Copper-free. Recommended for stainless steel and other metal fittings. For preventing corrosion, seizing and galling in harsh, chemical environments, and temperatures to 2400° F (1315°C).

Container Size	Order No.	Price
8 oz. Brush Top	77124	
1 lb. Brush Top	77164	



Silver Grade Anti-Seize
Heavy duty, temperature-resistant, petroleum-based lubricant compound fortified with graphite and metallic flake. Inert, will not evaporate or harden in extreme cold or heat. For use in assemblies up to 1600°F (871°C).

Container Size	Order No.	Price
8 oz. Brush Top	76732	
1 lb. Brush Top	76764	



Graphite-50 Anti-Seize
Electrically conductive, non-metallic. Temperature resistant up to 900°F (482°C). Highly electrically conductive in metal-to-metal joints.

1 lb. Can	Order No. 9951084	Price:
-----------	-------------------	--------

While we show only the popular **LOCTITE** items we can supply their entire range of products; please inquire.

RETAINING COMPOUNDS

609 Retaining Compound
General-purpose low viscosity retaining compound that bonds rigid metal assemblies. Ideal for gap distances up to 0.005" diameter. Fixtures in 10 minutes and provides a shear strength of 3,000 psi after 24 hours. Easily joins dissimilar metals. Withstands temperatures to 300°F.



Container Size	Order No.	Price
0.5 ml Capsule	60905	
10 ml. Bottle	60921	
50 ml. Bottle	60931	
250 ml. Bottle	60941	

680 Retaining Compound
High Strength/High Viscosity. A retaining compound for joining fitted cylindrical parts. Fixtures in 10 minutes and provides a shear strength of 4,000 psi on steel after 24 hours. Fills diametral gap distances up to 0.015".



Container Size	Order No.	Price
10 ml. Bottle	68015	
50 ml. Bottle	68035	
250 ml. Bottle	68060	

CLEANER

Electrical Contact Cleaner
Removes grease, oil and other contaminants from electrical parts to prevent contact failure. Dries residue-free in seconds. Non-conductive, non-corrosive, non-flammable. Contains no CFCs or Class I ODCs. Contains HCFC-141 b. May attack some sensitive plastics.



15 oz. Aerosol	Order No. 24379	Price:
----------------	-----------------	--------

SPECIALTY FLUIDS



SPECIALTY CUTTING AND TAPPING FLUIDS

SERIES 460:



ALL 55 GALLON DRUMS SHIPPED F.O.B. FACTORY

TAPFREE EXCEL CUTTING AND TAPPING FLUID

Tapfree Excel is a high performance cutting oil that is safe for use on all metals. Formulated with a unique blend of low odor extreme pressure additives, Tapfree Excel is pleasant to work with and produces exceptional results especially on hard to cut metals such as stainless steel, titanium and exotic alloys.

- High performance cutting oil formulated to produce tighter tolerances, longer tool life and a better surface finish on all metals.
- Especially effective on difficult to machine metals such as stainless steel, titanium and exotic alloys.
- Clings to the cutting tool for better hold on horizontal operations and less product usage.
- Low odor extreme pressure additives make Tapfree Excel pleasant to work with.



Size	Units per case	Order No.	Price
4 oz. Bottle (.118L)	24	4600005	
8 oz. Bottle (.236L)	12	4630308	
16 oz. Bottle (.473L)	12	4630316	
Gallon Jug (3.78L)	4	4630328	
5 Gallons (18.9L)	1 Pail	4630305	
30 Gallons (114L)	1 Drum	4630330	
55 Gallons (208L)	1 Drum	4630355	

TAPFREE 2 CUTTING AND TAPPING FLUID

Tapfree 2's Environmentally Safe HYDRO-LUBE formulation offers remarkable performance in a water based cutting fluid. Easy, precise cutting and quick cleanup make Tapfree 2 the preferred choice for production jobs, maintenance repairs and use on construction sites. Especially effective on low and medium carbon steel, cast iron, milder grades of stainless steel and alloy steels.

- Proprietary Hydro-Lube formulation delivers amazingly efficient cutting action, reduces heat buildup, and extends tool life.
- Produces a superior finish and tight tolerances on most production metals from aluminum to stainless steel; not for use with magnesium.
- Easy to clean up - light residue is wiped away with a damp rag.
- Environmentally Safe formula better for workers and the environment.



Size	Units per case	Order No.	Price
4 oz. Bottle (.118L)	24	4600008	
8 oz. Bottle (.236L)	12	4620208	
16 oz. Bottle (.473L)	12	4620216	
Gallon Jug (3.78L)	4	4620228	
5 Gallons (18.9L)	1 Pail	4620205	
30 Gallons (114L)	1 Drum	4620230	
55 Gallons (208L)	1 Drum	4620255	

NEW ALUMTAP CUTTING AND TAPPING FLUID

New Alumtap is a special compound that enables speedy and precise machining of aluminum. It has exceptional penetrating and lubricating qualities that reduce galling and extend tool life while improving fit and finish. It is the best cutting fluid available for use on aluminum, magnesium, copper, and other soft metals.

- Specifically formulated for the machining characteristics of aluminum and other soft metals.
- Produces an ultrafine surface finish that is clean and bright without metal smear or staining.
- Increases tool life by inhibiting spot welding and reducing the tendency of aluminum to adhere to the cutting edge of the tool.
- The answer to "problem" aluminum jobs that require tight tolerance.



Size	Units per case	Order No.	Price
4 oz. Bottle (.118L)	24	4600006	
16 oz. Bottle (.473L)	12	4660616	
Gallon Jug (3.78L)	4	4660628	
5 Gallons (18.9L)	1 Pail	4660605	
30 Gallons (114L)	1 Drum	4660630	
55 Gallons (208L)	1 Drum	4660655	

CLEANTAP CUTTING AND TAPPING FLUID

Cleantap is a synthetic, aqueous based cutting fluid developed for use on operations where the presence of certain chemicals cannot be tolerated. It improves cutting performance without the use of chlorine, sulphur, silicone or oil. Recommended for plastics and all jobs where corrosion is of prime concern.

- Contains a non-corrosive extreme pressure additive that helps keep tools sharp and improves surface finish.
- Does not contain oil, chlorine, sulfur or silicone.
- Will not corrode or stain any ferrous or nonferrous metal and will not craze plastics.
- Easy to clean up - light residue is wiped away with a damp rag.



Size	Units per case	Order No.	Price
4 oz. bottle (.118L)	24	4600007	
16 oz. Bottle (.473L)	12	4650516	
Gallon Jug (3.78L)	4	4650528	
5 Gallons (18.9L)	1 Pail	4650505	
30 Gallons (114L)	1 Drum	4650530	
55 Gallons (208L)	1 Drum	4650555	

SPECIALTY FLUIDS



TAPPING & CUTTING FLUIDS, ETC.

SERIES 689:



ALL 55 GALLON DRUMS SHIPPED F.O.B. FACTORY

SPECIALTY FLUIDS

TAPMATIC TRICUT®

Clear plastic bottles allow end users to quickly check volume levels.

- Available in liquid or paste
- Suitable for most metals; excellent for stainless steel
- Extends tool life
- Reduces production costs
- Improves surface finish
- Allows increased removal rates
- Reduces friction
- Flows directly to cutting edge
- Suitable for high and low speed applications
- Provides smooth, accurate cutting action
- Is non-corrosive to steel



Size	Order No.	Price
16 fl. oz. liquid (0.473 liter)	6005316	
1 gal. liquid (3.78 liters)	6005328	

TAPMATIC NATURAL

Meets USDA requirements for P1.

- Nontoxic, nonhazardous and biodegradable
- Does not irritate the skin, eyes or respiratory tract
- Does not contain 1,1,1 trichloroethane, sulfur, chlorine, chlorinated solvents, water, mineral oil or inactive fillers
- High performance lubricating ability eliminates galling and seizing
- Safe on all metals



Size	Order No.	Price
16 fl. oz. (0.473 liters)	6044220	
1 gal. (3.78 liters)	6044230	
5 gal. (18.93 liters)	6044240	
55 gal. (208 liters)	6044260	

TAPMATIC EDGE LIQUID

Meets USDA requirements for P1.

Edge liquid replaces flood coolants and eliminates disposal costs.

- Compatible with drop applicators
- High film strength
- Reduces friction
- Compatible with oil and water systems
- Replaces flood coolants and eliminates disposal costs
- Low toxicity
- Increases tool life
- Safe on all metals
- Excellent for high alloy metals



Size	Order No.	Price
16 fl. oz. (0.473 liters)	8943020	
1 gal. (3.78 liters)	8943030	

TAPMATIC #1 GOLD

Meets USDA requirements for P1.

- Great for hard to machine metals
- Excellent for low speed, high pressure applications
- Minimizes torque increases
- Does not contain 1,1,1 trichloroethane, chlorinated paraffins, water, solvents or inactive fillers
- Aerosol provides a pinpoint stream with foaming action
- Safe on all metals



Meets or exceeds these specs:

Boeing BAC 5008

Boeing D6-48809

Size	Order No.	Price
16 fl. oz. (0.473 liters)	6040320	
11 oz. (312 g.) aerosol	6040312	
1 gal. (3.78 liters)	6040330	
5 gal. (18.93 liters)	6040340	
55 gal. (208 liters)	6040360	

TAPMATIC AQUACUT

Meets USDA requirements for P1.

- Water-based formula
- Excellent for high speed, low pressure applications
- Nonflammable
- Nonhazardous
- Does not contain 1,1,1 trichloroethane, sulfur, chlorine or oils
- Safe on all metals, except magnesium
- Corrosion inhibitors prevent flash rusting
- Provides fine finishes. Cinnamon scent



Size	Order No.	Price
16 fl. oz. (0.473 liters)	6001216	
1 gal. (3.78 liters)	6001228	
5 gal. (18.93 liters)	6001205	

TAPMATIC EDGE LUBE AND CREME

Meets USDA requirements for P1.

Edge Lube:

- Excellent for belt, wheel and disc grinding or sawing applications.
- White, solid waxy bar

Edge Creme:

- Excellent for vertical applications
- For use when drilling, tapping blind holes, forming, bending, pre-coating fasteners and lubricating rubber seals.
- Squeeze tube allows easy usage

Both:

- Biodegradable
- Eliminates heat buildup and belt loading
- Does not contain any hazardous chemicals
- Compatible with oil and water systems
- Extends grinding wheel life
- Low toxicity
- Safe on all metals



Description	Size	Order No.	Price
Edge Lube	13 oz. (364 grams)	8943200	
Edge Creme	11 oz. (.325 liters)	8943100	



CUTTING AND GRINDING FLUIDS AND OILS



SERIES 691:

ALL 55 GALLON DRUMS SHIPPED F.O.B. FACTORY

While we show only the popular **RUSTLICK** items we can supply their entire range of products; please inquire.

ULTRACUT 250R & 255R

CHARACTERISTICS

Safe, Biostable, Water Soluble Oils

- 250R - Contains Non-Chlorinated EP additives only
- 255R - Contains Chlorinated and Non-Chlorinated EP additives
- Provides long sump life
- Low foaming

APPLICATIONS

250R - General purpose, medium duty applications

255R - High Performance/severe applications including hard to machine alloys

- Can be used on all metals



Description	250R		255R	
	Order No.	Price	Order No.	Price
1 Gal (4/case)	9174615		-	
5 Gal	9174605		9174705	
55 Gal	9174655		9174755	

WS-5050

CHARACTERISTICS

Heavy duty soluble oil

- Effective chlorinated E.P. additive provides excellent tool life
- Special additives protect neoprene seals

APPLICATIONS

General purpose, medium/severe duty applications

- Can be used on all ferrous metals
- Not recommended for Titanium
- Compatible with CNC machining



Description	Order No.	Price
1 Gal (4/case)	9174016	
5 Gal	9174056	
55 Gal	9174556	

WS-500A

CHARACTERISTICS

Chlorine free soluble oil

- Designed with a proprietary E.P. additive
- Does not contain chlorine or active sulfur, thereby reducing disposal cost

APPLICATIONS

Excellent for general machining

- Good for Titanium, Inconel X, Aluminum, Rene 41, Stainless Steel and other metals
- Compatible with CNC machining



Description	Order No.	Price
5 Gal	9174055	
55 Gal	9174555	

WS-11

CHARACTERISTICS

Non-Chlorinated soluble oil

- An economical soluble oil

APPLICATIONS

General purpose, medium-duty applications

- Can be used as a light film rust preventative



Description	Order No.	Price
1 Gal	9174013	
5 Gal	9174053	
55 Gal	9174553	

SS-405L

CHARACTERISTICS

Semi-synthetic coolant

- Provides excellent lubricity and protects machines & parts from rust

APPLICATIONS

General purpose, for machining and grinding

- Can be used on many different metals including Aluminum



Description	Order No.	Price
5 Gal	9178405	
55 Gal	9178410	

VYTRON-N

CHARACTERISTICS

Synthetic coolant

- High level of rust prevention
- Long sump life prevents rancidity

APPLICATIONS

General purpose, machining and grinding on ferrous metals

- Setting the standard for over 20 years



Description	Order No.	Price
1 Gal (4/ case)	9175014	
5 Gal	9175054	
55 Gal	9175554	

G-25-J

CHARACTERISTICS

Grinding Synthetic coolant

- High level of rust prevention, non-foaming, transparent
- Enables the rapid settling of residues, which eliminates wheel buildup and ensures finer finishes

APPLICATIONS

General purpose, designed for grinding applications

- Excellent for Blanchard grinding



Description	Order No.	Price
1 Gal (4/case)	9175012	
5 Gal	9175052	
55 Gal	9175552	

CARBIDE POWERGRIND

CHARACTERISTICS

Synthetic carbide grinding fluid

- Cobalt leaching is minimal providing worker health and safety
- Its excellent lubricity and flushing keep grinding wheels clean
- High level of rust prevention

APPLICATIONS

High Performance Carbide Grinding Coolant

- Formulated to minimize the leaching of cobalt from carbide and to prevent chemical damage to carbide in grinding applications
- Can be used with all metals except magnesium



Description	Order No.	Price
5 Gal	9174052	
55 Gal	9174552	



EDM OILS: CLEANERS AND COOLANT MANAGEMENT



SERIES 691:

ALL 55 GALLON DRUMS SHIPPED F.O.B. FACTORY

EDM-250

CHARACTERISTICS - Dielectric Oil

- Low viscosity for excellent flushing and finishing
- Virtually odorless

APPLICATIONS

EDM machining, good for all filters

- Resists thermal degradation from high-amperage applications up to 400 amps

Description	Order No.	Price
55 Gal	9172550	



EDM-30

CHARACTERISTICS - Dielectric Oil

- Low viscosity allows for fast settling that yields higher quality finishes

APPLICATIONS

EDM machining

- Designed for paper cartridge filtration up to 150 amps

Description	Order No.	Price
5 Gal	9172052	
55 Gal	9172552	



KLEENZOL DY

CHARACTERISTICS - Water Soluble Alkaline Cleaner

- Non-flammable, non-toxic and biodegradable

APPLICATIONS

- Sump cleaner that quickly penetrates and dislodges grimy buildups of chips and oil residues

Description	Order No.	Price
1 Gal(4/case)	9176012	
5 Gal	9176052	
55 Gal	9176552	



GROTAN

CHARACTERISTICS - Broad Spectrum Bactericide

APPLICATIONS

- Provides added protection to extend coolant life.
- For use in individual sumps and large central systems.
- Helps protect machines, tools and workpieces from corrosion.
- Controls bacteria and fungus growth

1 Gal (4/case)

Order No.	Price
9177011	



TRAMP OIL SKIMMER

Tramp oils seal the surface of the coolant in your sump against air, providing an ideal growth environment for the microorganisms, which cause a host of problems. The tramp oil skimmer removes these oils at a rate of up to 1-1/2 gallons per hour automatically, reliably and economically.

Description	Order No.	Price
12" Skimmer	9178012	
18" Skimmer	9178018	



CNC SKIMMER - SC3000

Coalescent Skimmer

This portable coolant skimmer removes up to 95% of floating tramp oils from machine tool sumps. Detachable floating oil skimmers have no positioning requirements, provide perfect fluid flow and are easily installed. With the SC3000, the entire coolant filtration process takes place quickly, without removing the machine from operation

- Portable design for easy relocation and all multiple machine use
- Prevention of rancidity and "Monday morning odor"
- One-time setup with equipment modification required
- Reduced coolant replacement and disposal costs



Description	Order No.	Price
SC3000 Coalescent Skimmer	9178100	
SC3000 Float (pair)	9178101	
SC3000 Filter cartridge	9178102	



Made In U.S.A.

SafeTap

TAPPING FLUIDS

SERIES 691:

Aerosols cannot be shipped by air.



Made In U.S.A.

SafeTap

SAFE TAP PLUS

SafeTap Plus is a unique blend of synthetic additive creating a water based tapping fluid. The purpose of SafeTap Plus is to improve tool life and give better threads in tapped holes while providing the worker with a safe and clean environment.

- Higher viscosity and lubricity
- High in rust protection
- No oily residue
- No mineral oils or solvents
- Water-based formula for easy clean-up
- Safe for all metals except magnesium



Description	Order No.	Price
4 oz. (24/case)	9171911	
16 oz. (12/case)	9171912	
1 Gal. (4/case)	9171913	
5 Gal.	9171914	

SAFE TAP ULTIMA

SafeTap Ultima is an ultra-clean, high performance, environmentally compatible tapping fluid.

- 100% biodegradable
- Water-Clear
- Non-staining and odorless
- Safe for all metals
- All natural ingredients

Description	Order No.	Price
16 oz. (12/case)	9171952	
1 Gal. (4/case)	9171953	
5 Gal.	9171954	



SPECIALTY AEROSOLS
SERIES 693:



AEROSOLS CANNOT BE SHIPPED BY AIR

Product	Description	Performance	Applications	Order No. Price	
CORROSION PREVENTATIVES -REMOVABLE PROTECTIVE COATINGS					
Tool & Die Saver 11 oz.	Greasy elastic film	Absorbs moisture, fortified with lanolin Neutralizes acid formed by corrosive atmosphere.	Good for chucks, set-up jigs, tools, and stored molds. Ideal for long-term and long-distance storage. Easy to remove.	6933090	
Rust Inhibitor 11 oz.	Greasy elastic film	Absorbs moisture, fortified with lanolin. Neutralizes acid formed by corrosive atmosphere.	Prevents rust on tools, steel stock, parts and temporary or extended protection of machinery. Good for indoor storage.	6936007	
LUBRICANTS AND COOLANT					
Cutting Oil 10.5 oz.	Light oil	All purpose lubricant and coolant.	Turret lathes, gear cutters, grinders, automatic screw machines, and pipe threaders.	6937020	
TOOL ROOM SUPPLIES					
Blue Tool-maker's Ink 12 oz.		Enables accurate scribing without glare. Produces a quick drying film that will not chip. May be scribed within 5 minutes of application.	For production layouts, patternmaking, tool, die, and modelmaking. May be used for templates and machined parts.	6946001	
Toolmaker's Ink Remover 10.5 oz.	Solvent spray for layout fluids	Removes ink without residue	Fast acting and quick removal of toolmaker's ink and layout fluids from the surface of completed work. Can also be used as a paint stripper.	6946095	
MISCELLANEOUS					
Drive Belt Dressing 12 oz.	Clear liquid	Increases gripping and pulling power. Stops slippage of all types of belts while stopping squeaks and squeals. Helps preserve leather and rubber.	For use on compressors, pumps, conveyors, generators, fans, textile, automotive and farm equipment.	6938079	
Tan Box Saver 12 oz.		A cost effective spray that dries quickly, surfaces appear new, won't rub off.	For use on cartons or to salvage carton overruns. Covers up old print, or light stains. Boxes can then be restenciled or relabeled.	6932811	

SPECIALTY FLUIDS

MILWAUKEE SURE SHOT
SERIES 639:

- 1 Qt. capacity
- All metal construction
- Rechargeable with compressed air
- Working Pressure 80-150 PSI
- Adjustable spray nozzle
- Great for degreasers, cleaners, solvents, rust inhibitors, etc.
- Not recommended for paints



ENVIRONMENTALLY SAFE • SAVE THE OZONE

- Refillable, Rechargeable
- Completely Portable
- Use Inexpensive Bulk Liquids, Eliminate Aerosol Disposal Problems
- Non Ozone-Depleting



Anything an aerosol sprays SURE SHOT sprays safer !
Just fill with liquid, pressurize with standard air chuck and spray

Order No. 6000059 Price

TOOL AND INSTRUMENT OIL
SERIES 789:



- 4 fl.oz. (0.1 liter) Plastic Bottle
- Assures maximum protection and lubrication of working parts.
- Especially useful for lubricating and protecting fine instruments, micrometers and other tools, light machinery and countless other applications.
- High-refining makes oil colorless.

Catalog No.	EDP No.	Price
1620	53216	

GORRILLA BRAND PREMIUM GLUE™
SERIES 526:



100% Solvent Free • Polyurethane
Absolutely the finest, strongest and most pure adhesive in the world.

- Bonds Metal, Ceramics, Wood, Stone, Plastics and more.
- Time tested polyurethane with 25 years of proven usage.
- Uses no thickeners, solvents or fillers
- Can be used indoors and out. (Only true waterproof glue)
- Sandable and stainable.
- Greater usable temperature range (40 to 130 degrees)
- 3 to 4 times the coverage of other glues.
- Virtually odorless.



4 oz. Bottle	Order No. 6050004	Price	
8 oz. Bottle	Order No. 6050008	Price	

M1 ALL PURPOSE LUBRICANT Starrett
SERIES 792:



A special formula originally developed by Starrett to protect high quality precision tools. M1 when applied produces a micro-thin air-tight coating film that simultaneously dries as it protects, avoiding dirt, grime, etc. that other "wet" lubricants actually attract.
SPRAYS UPSIDE DOWN: The can will spray upside down in awkward places without losing propellant power.

LUBRICATES: M1 is free of silicone, making it an excellent lubricant that is also easily removed to prep surfaces for paint. Its ability to stand up to extreme temperatures makes it ideal year-round.

PENETRATES: Deep-down penetration works quickly to free frozen nuts, bolts and metal parts. Actually gets under caked-on dirt to the clean metal.

PREVENTS RUST: Protects metal against rust and corrosion damage for months by providing a molecular shield that locks to the metal.

CLEANS: Actually removes grease, tar and grime from metal parts and painted surfaces. Cleans and polishes for lasting protection.

STOP SQUEAKS: Has instant lubrication properties that spread into hard to - reach metal parts to stop squeaking and sticking.

DISPLACES MOISTURE: M1 is not soluble in water, so it gets under moisture to lift it away from the surface to be protected.

NON- CONDUCTIVE: Prevents short circuits in high moisture environments. Halts electrical leakage from wet ignition wires.

ENVIROMENTALLY FRIENDLY: Contains no harmful fluorocarbons/detergents and is also FDA approved for using in or near food-related environments.

Description	Catalog No.	EDP No.	Price
12 oz aerosol can	M1-95173	95173	
1 gallon container	M-1.01	93221	
5 gallon pail	M-1.05	93227	
53 gallon drum	M-1.53	93233*	
1 pint bulk spray dispenser, empty	M-1.15	93251	

*F.O.B. Factory

SIMPLE GREEN®
SERIES 249:



Cleaner / Degreaser

Biodegradable, non-flammable, non-abrasive, non-toxic concentrate that can be custom-diluted to economically tackle any cleaning job. Safer alternative to hazardous chemicals and solvents. Exempt from OSHA and EPA special handling and personnel protection requirements for hazardous chemicals. Meets Federal Clean Air Act.

Simple Green-All Purpose Cleaner/Degreaser has a pleasant sassafras scent. Contains no petroleum distillates. Authorized by USDA for use in federally inspected meat and poultry plants.
Crystal Simple Green-Industrial Strength Cleaner/Degreaser for critical cleaning applications that demand a clear and fragrance-free solution. Ideal for industrial /manufacturing, electronics and parts washers. Meet FDA requirements for cleaning in cosmetic, medical and pharmaceutical environments.



55 gal. drums shipped F.O.B. factory.

Size	Case Qty.	Order No.	Price
Simple Green-All Purpose Cleaner/Degreaser			
24oz. Spray Bottle	12	4113012	
1 gal. Bottle	6	4113005	
5 gal. Pail	1	4113006	
55 gal. Drum	1	4113008	
Crystal Simple Green-Industrial Strength Cleaner/Degreaser			
24oz. Spray Bottle	12	4119024	
1 gal. Bottle	6	4119128	
5 gal. Pail	1	4119005	
55 gal. Drum	1	4119055	