

AEROSOLS CANNOT BE SHIPPED BY AIR



Tel: 201-518-8461 / Fax: 201-596-3427

650 Huyler St / So. Hackensack, NJ 07606 USA

## LIQUID THREADLOCKERS

### 262 Threadlocker

Medium to High Strength A permanent locking threadlocker for fasteners up to 3/4" (20mm) diameter. High lubrication for easy assembly. Excellent for preventing rust and corrosion in extreme chemical/environmental conditions.

| Container<br>Size                              | Order<br>No.            | Price |
|--|-------------------------|-------|
| 10 ml. Tube<br>50 ml. Bottle<br>250 ml. Bottle | 26221<br>26231<br>26241 |       |

## 242<sup>®</sup> Threadlocker

Medium Strength

A general-purpose, removable threadlocker for fasteners between 1/4" and 3/4" (6 to 20 mm) diameters. Controlled lubricity for accurate clamp loads. Parts can be separated using hand tools.

| Container<br>Size                                | Order<br>No.            | Price |
|--|-------------------------|-------|
| 10 ml. Bottle<br>50 ml. Bottle<br>250 ml. Bottle | 24221<br>24231<br>24241 |       |

### 222 MS Threadlocker

Low Strength/Small Screw Ideal for fastener diameters of 1/4" (6mm) and smaller. Controlled lubricity for accurate clamp loads. Parts can be separated using hand tools.

| Container<br>Size                                | Order<br>No.            | Price |
|--|-------------------------|-------|
| 10 ml. Bottle<br>50 ml. Bottle<br>250 ml. Bottle | 22221<br>22231<br>22241 |       |

## SURFACE PREPARATION

#### 7649 Primer N

A solvent-based primer that features very long on-part life. Decreases the set-up time of Loctite<sup>®</sup> Threadlockers and increases breakaway torque on most fastener surfaces. Ideal for cure conditions below room temperature.

| Container<br>Size   | Order<br>No.            | Price | 1007/1   |
|---|-------------------------|-------|--|
| 25 gm. Aerosol Can<br>1.75 fl oz. Bottle<br>4.5 oz. Aerosol Can | 21347<br>19269<br>21348 |       | 764<br>PRMER<br>PANER N<br>WARNING: Harri<br>Swallowed Frank |

#### 565 PST<sup>®</sup> THREAD SEALANT <u>Controlled Strength</u> A general-purpose instant sealant for tapered and straight/tapered fittings. Controlled strength for ease of disassembly.

| 50 ml. Tube     |  |  |
|-----------------|--|--|
| Order No. 56531 |  |  |
| Price:          |  |  |

**THREAD SEALANT** 



## **BONDING ADHESIVES**

**454 PRISM®** <u>Surface Insensitive Instant</u> Adhesive Gel

A General-purpose, no-run clear gel. Can be applied to vertical surfaces. Excellent for almost all surfaces. Ideal for porous substrates and rough and acidic surfaces.

### 495 SUPER BONDER®

Instant Adhesive A general-purpose adhesive designed to bond rubber, metal and plastic parts with gaps to .004".

| Product<br>No. | Order Container<br>No. Size |             | Price |
|----------------|-----------------------------|-------------|-------|
| 454            | 9945404                     | 3 gm Tube   |       |
| 454            | 45440                       | 20 gm Tube  |       |
| 495            | 49504                       | 3 gm Tube   |       |
| 495            | 49550                       | 1 oz Bottle |       |

# COATING

### Color Guard®

Tough Rubber Coating

Inhibits rust and corrosion; seals, insulates and identifies almost any material in minutes. Creates a non-slip gripping surface. Rubber coating won't crack or chip. Acid and alkali resistant. Lasts for years. Use to 200°F. Dip, spray or brush to apply. Suggested applications include: Tools, metal, electrical connections, masonry, wood, conveyors, glass, rope, fabric.



| Size         | Black | Blue  | Red   | Yellow | Price |
|--------------|-------|-------|-------|--------|-------|
| 14.5 oz. Can | 34979 | 34982 | 34985 | 34988  |       |

While we show only the popular **LOCTITE** items we can supply their entire range of products; please inquire.



